

DATASHEET

23mm FireSafe



A multi-laminated glass assembled with clear intumescient interlayers. These layers expand and turn into a rigid and opaque fire shield at around 120°C, meeting the integrity criterion of EN 1363.

Technical Data

FireSafe

| | |
|--------------------------|------------------------|
| Fire Classification | EI60 |
| Glazing Type | Single |
| Grade | Internal |
| Thickness | 23 mm |
| Thickness Tolerance | ±1 mm |
| Dimensional Tolerance | ±2 mm |
| Weight | 57.6 kg/m ² |
| Light Transmission (%) | 82 |
| UV Protection | No |
| Safety Rating (EN 14449) | Class I(B)I |
| Sound Reduction | 40 dB |

Key Features

- ✓ Fire resistant EI60
- ✓ 60 minutes Integrity/60 minutes Insulation
- ✓ Interior and exterior use dependant on glass type
- ✓ Steel, aluminium and timber applications
- ✓ Glazing integrity criterion EN 1363
- ✓ Multi-laminated



For more information about our products, give us call us on **0121 521 2180** or visit www.fireglassuk.com

NATIONWIDE BRANCHES

| UK | NORTH | EAST | SOUTH | SCOTLAND |
|-----------------------------|-----------------------------|------------------------|-----------------------------|----------------------------|
| Birmingham 0121 521 2180 | Manchester 0161 728 8080 | Derby 01773 712 920 | Colchester 01206 222 090 | Edinburgh 0131 526 4141 |