## SPECIALISTS IN FIRE RATED GLASS AND GLAZING

tel 0121 667 9089 email info@fireglassuk.com

## WWW.FIREGLASSUK.COM





TECHNICAL FIRE SAFETY GROUP



## DATA SHEET 10MM CLEAR TOUGHENED

10mm Clear Toughened is a high quality clear, toughened float glass which is fully recyclable. Ideal for a variety of applications in the exterior and interior of buildings.

## TECHNICAL INFORMATION

Resistance to Fire	NPD
Reaction to Fire	A1
External Fire Performance	NPD
Bullet Resistance	NPD
Explosion Resistance	NPD
Burglar Resistance	NPD
Pendulum Body Impact Resistance	1(C)1
Resistance Against Sudden Temperature Changes and Temperature Differentials	40K
Wind, Snow, Permanent and Imposed Load Resistance	10MM
Direct Airbourne Sound Insulation	33(-2;-3)dB
Thermal Properties	5.6W/(m²,K)
Radiation Properties	
Light Transmittance/ Reflectance	0.89/0.08
Solar Energy Transmission/ Reflectance	0.80/0.08
g Value	0.77
Durability	Pass
Normal Emissivity	0.89/0.89
NPD = NO PERFORMANCE DETERMINED. NOTIFIED PRODUCTION CONTROL CERTIFICATION BODY NUMBER 1750	

**KEY FEATURES** 

		Highest quality float glass
		Very high light transmission
		Easily processed and fabricated
		Manufactured in accordance with EN 572-2
		Fully recyclable.
	CL III	
		TABLE APPLICATION
		Can be used in IGUs with other products to achieve additional benefits.
		Internal and External.
STORAGE AND HANDLING		
	510	
	au b	Must be handled with care during transportation, storage, inspection and installation.
		If you need help, please email: technical@fireglassuk.com







Fire Glass UK Limited. Part of the Technical Fire Safety Group. Registered in England No. 6737753 at: 24-26 Hainge Road, Oldbury, West Midlands B69 2NH.

firas

certifire

Constructionline