



DATA SHEET

6.8MM ACOUSTIC LAMINATED

Comprising of two or more panes of glass which are bonded together using a specially designed high performance clear PVB interlayer. Various performances can be achieved by combing different types of glass thickness and number of interlayers.

TECHNICAL INFORMATION

Resistance to Fire	NPD
Reaction to Fire	NPD
External Fire Performance	NPD
Bullet Resistance	NPD
Explosion Resistance	NPD
Category of Resistance (EN 356)	P2A
Pendulum Body Impact Resistance	1(B)1
Resistance Against Sudden Temperature Changes and Temperature Differentials	40K
Wind, Snow, Permanent and Imposed Load Resistance	6 mm
Direct Airborne Sound Insulation	35 dB

THERMAL PROPERTIES

Thermal Transmittance (U-value)	5.7 W/(m ² ,K)
---------------------------------	---------------------------

RADIATION PROPERTIES

Light Transmittance	0.89
Light Reflection	0.08
Solar Energy Transmission	0.77
Solar Energy Reflection	0.07








NPD = NO PERFORMANCE DETERMINED

KEY FEATURES

- ✓ Break safe characteristics
- ✓ Resists attack
- ✓ UV protection
- ✓ Improved acoustic performance
- ✓ Manufactured in accordance with EN 14449
- ✓ Minimised UV-transmission
- ✓ Sound control

If you need help with any technical specifications, please email: technical@fireglassuk.com
We will be happy to help.

LOCAL BRANCH NETWORK

						
MIDLANDS	NORTH	SOUTH	EAST	WEST	SCOTLAND	INSTALLATION
0121 667 9089	0161 532 8371	01206 805 922	0121 667 9089	01174 528 800	0131 526 4141	0121 667 9089

