



DATASHEET

7MM FIRE SWISS COOL

Fire Swiss Foam offers protection against fire and smoke at reduced heat radiation.

TECHNICAL INFORMATION

Fire Classification	EW30
Glazing Type	Single
Grade	Internal
Thickness	7 mm
Thickness Tolerance	±1 mm
Dimensional Tolerance	±2 mm
Weight	22 kg/m ²
Light Transmission (%)	89
UV Protection	No
Safety Rating (EN 14449)	Class 3(B)3
Sound Reduction	35 dB

KEY FEATURES


30
0


- Fire Resistant E30
- 30 minutes Integrity
- Interior only
- Low radiation glass
- Glazing to Integrity Criterion EN 1363

SUITABLE APPLICATION

- Can be used in steel & timber applications

STORAGE AND HANDLING

-  Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

-  If you need help, please email: technical@fireglassuk.com



FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

NATIONWIDE BRANCHES

UK

BIRMINGHAM
0121 521 2180

NORTH

MANCHESTER
0161 728 8080

EAST

DERBY
01773 712 920

SOUTH

COLCHESTER
01206 222 090

SCOTLAND

EDINBURGH
0131 526 4141

INSTALLATION

BIRMINGHAM
0121 521 2180

