



DATA SHEET

7MM FIRE SWISS COOL

Fire Swiss Foam offers protection against fire at reduced heat radiation.

TECHNICAL INFORMATION

Fire Classification	EW30
Glazing Type	Single
Grade	Internal
Thickness	7 mm
Thickness Tolerance	±1 mm
Dimensional Tolerance	±2 mm
Weight	22 kg/m ²
Light Transmission (%)	89
UV Protection	No
Safety Rating (EN 14449)	Class 3(B)3
Sound Reduction	35 dB

30
0


KEY FEATURES


- Fire Resistant E30
- 30 minutes Integrity
- Interior only
- Low radiation glass
- Glazing to Integrity Criterion EN 1363

SUITABLE APPLICATION

- Can be used in steel & timber applications

STORAGE AND HANDLING

-  Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

-  If you need help, please email: technical@fireglassuk.com

! FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: TECHNICAL@FIREGLASSUK.COM

ACCREDITATION & CERTIFICATION

